

# SL150



SL150 is a snap lock standing seam roof panel with 1.5" high ribs that installs with concealed clips. The clips allow the panel to freely expand and contract during thermal movement which can help ensure an aesthetically pleasing look when very long panel lengths are required. SL150 is popular in both residential and commercial applications and is a great choice for customers that prefer a taller rib profile or for roofs requiring very long panel lengths.

### Specifications:

- Standing seam concealed fastener panel for roof applications.
- Snap locking ribs.
- Installs with clips.
- 3:12 minimum recommended roof pitch.
- Suitable for solid decking.

### Substrates and Coatings:

- 26 and 24 gauge high strength steel.
- 0.032" aluminum.
- Anti-corrosion AZ50 Galvalume® coating for painted and AZ55 for unpainted steel.
- 26 ga available in 45 Year and Lifetime Siliconized Modified Polyester Paint Systems.
- 24 ga and aluminum available in PVDF (Kynar 500 or Hylar 5000) Paint System.

### Testing and Approvals:

- UL 580 Construction #589.
- UL Class 4 Impact.
- UL 790 Fire Resistance Class A.
- ASTM E-283 Air, E-331 Water.
- Florida Building Code Approved:
  - 9443.1 – 24 ga over 15/32" plywood.
  - 18716.2 – 0.032" aluminum over 7/16" OSB or 15/32" plywood.

